

# Commercial Softeners

The **ATS Series 2750** and **Series 2850 Commercial Softeners** are suitable for large residential as well as light commercial applications using single or multiplex systems up to 55 gpm flow rates per single tank system.

The **ATS Series 2900** and **Series 3900 Commercial Softeners** are high flow single or multiplex systems providing performance and versatility to commercial and industrial applications up to 350 gpm flow rates per single tank systems.



**3200 NXT  
Network Controller**

## DIMENSIONS

Model #	Height	Width	Length (Single)	Length (Dual)
NXT90-1	71½"	19"	39"	59"
NXT90-1.5	71½"	19"	39"	59"
NXT120-1	71½"	25"	47"	69"
NXT120-1.5	71½"	25"	47"	69"
NXT150-1	71½"	25"	49"	73"
NXT150-1.5	71½"	25"	49"	73"
NXT210-1	73½"	25"	52"	79"
NXT210-1.5	73½"	25"	52"	79"
NXT300-1.5	80½"	32"	62"	92"
NXT450-1.5	84½"	41"	77"	113"
NXT90-2	76¾"	19"	39"	59"
NXT120-2	76¾"	25"	47"	69"
NXT150-2	76¾"	25"	49"	73"
NXT210-2	79½"	25"	52"	79"
NXT300-2	86½"	32"	62"	92"
NXT300-3	92"	32"	62"	92"
NXT450-2	95"	41"	77"	113"
NXT450-3	96"	41"	77"	113"
NXT660-2	97"	41"	83"	125"
NXT660-3	98"	41"	83"	125"
NXT900-3	100"	44"	92"	140"
NXT1200-3	100½"	55"	109"	163"
NXT1500-3	110½"	57"	125"	196"



MADE IN U.S.A.



*Providing Better Water For Better Living.*

# Commercial Softeners

## SPECIFICATIONS

Model #	Exchange		Resin Cu./ Ft.	Pipe Size	Flow		BW GPM	Tank Size		Salt Cap.	Salt Usage	
	Max.	Min.			Cont.	Peak		Mineral	Brine		Max.	Min.
NXT90-1	90K	60K	3	1"	19	26	5	14" x 65"	18" x 40"	300	45	18
NXT90-1.5	90K	60K	3	1½"	30	41	5	14" x 65"	18" x 40"	300	45	18
NXT120-1	120K	80K	4	1"	20	27	7	16" x 65"	24" x 41"	530	60	24
NXT120-1.5	120K	80K	4	1½"	33	45	7	16" x 65"	24" x 41"	530	60	24
NXT150-1	150K	100K	5	1"	20	27	9	18" x 65"	24" x 41"	500	75	30
NXT150-1.5	150K	100K	5	1½"	34	47	9	18" x 65"	24" x 41"	500	75	30
NXT210-1	210K	140K	7	1"	20	27	10	21" x 62"	24" x 50"	560	105	42
NXT210-1.5	210K	140K	7	1½"	36	49	10	21" x 62"	24" x 50"	560	105	42
NXT300-1.5	300K	200K	10	1½"	40	54	15	24" x 72"	30" x 50"	850	150	60
NXT450-1.5	450K	300K	15	1½"	44	55	20	30" x 72"	39" x 48"	1460	225	90
NXT90-2	90K	60K	3	2	39	54	5	14" x 65"	18" x 40"	300	45	18
NXT120-2	120K	80K	4	2	47	64	7	16" x 65"	24" x 41"	530	60	24
NXT150-2	150K	100K	5	2	53	70	9	18" x 65"	24" x 41"	500	75	30
NXT210-2	210K	140K	7	2	60	77	10	21" x 62"	24" x 50"	560	105	42
NXT300-2	300K	200K	10	2	68	91	15	24" x 72"	30" x 50"	850	150	60
NXT300-3	300K	200K	10	3	120	170	15	24" x 72"	30" x 50"	850	150	60
NXT450-2	450K	300K	15	2	84	105	20	30" x 72"	39" x 48"	1460	225	90
NXT450-3	450K	300K	15	3	158	190	20	30" x 72"	39" x 48"	1460	225	90
NXT660-2	660K	440K	22	2	84	105	30	36" x 72"	39" x 48"	1200	330	132
NXT660-3	660K	440K	22	3	185	250	30	36" x 72"	39" x 48"	1200	330	132
NXT900-3	900K	600K	30	3	200	268	45	42" x 72"	42" x 60"	1800	450	180
NXT1200-3	1200K	800K	40	3	213	280	60	48" x 72"	50" x 60"	2700	600	240
NXT1500-3	1500K	100K	50	3	267	350	75	63" x 86"	50" x 60"	2250	750	300

Note: Larger Brine Tank may be needed. For maximum salt settings, please consult the factory.

