

Commercial Alternating

The **ATS Series 9000, 9500 Commercial Softeners** are 1.5" alternating system using a single control valve for commercial applications up to 48 gpm flow rate.



DIMENSIONS

Model #	Height	Width	Length	Weight
DT9-2	47"	17"	47"	220
DT9-3	61"	17"	47"	300
DT9-4	59½"	17"	51"	375
DT91-2	47"	17"	47"	220
DT91-3	61"	17"	47"	300
DT91-4	59½"	17"	51"	375
DT91-5	71"	18"	56"	515
DT91-6	71"	18"	60"	645
DT95-14	73"	19"	59"	590
DT95-16	72¼"	25"	69"	720
DT95-18	73"	25"	75"	855
DT95-21	74½"	25"	79"	970
DT95-24	81½"	32"	92"	1590



Electronic
Totalizer (XT)

FEATURES

- Composite Fiberglass Construction Tanks
- Time Adjustable 5 cycle Down Flow Brine Control
- Backwash Capability up to 24" Diameter Tank
- Rugged Brass Body Valve
- XT Timers come standard
- 24 Hour Conditioned Water
- High Salt Efficiency
- Filter, Hot Water, Dealkalizer Application Options



MADE IN U.S.A.



Providing Better Water For Better Living.

Commercial Alternating

SPECIFICATIONS

Model #	Exchange		Resin Cu./ Ft.	Pipe Size	Flow		BW GPM	Tank Size		Salt Cap.	Salt Usage	
	Max.	Min.			Cont.	Peak		Mineral	Brine		Max.	Min.
DT9-2	30K	20K	1	¾"	8	12	2.4	10" x 40"	15" x 33"	275	15	6
DT9-3	45K	30K	1.5	¾"	9	16	2.4	10" x 54"	15" x 33"	275	22.5	9
DT9-4	60K	40K	2	¾"	10	18	3.5	12" x 52"	15" x 33"	275	30	12
DT91-2	30K	20K	1	1"	8	12	2.4	10" x 40"	15" x 33"	275	15	6
DT91-3	45K	30K	1.5	1"	9	16	2.4	10" x 54"	15" x 33"	275	22.5	9
DT91-4	60K	40K	2	1"	10	18	3.5	12" x 52"	15" x 33"	275	30	12
DT91-5	90K	60K	3	1"	14	20	5	14" x 65"	18" x 40"	300	45	18
DT91-6	120K	80K	4	1"	18	24	7	16" x 65"	24" x 41"	530	60	24
DT95-14	90K	60K	3	1½"	14	22	5	14" x 65"	18" x 40"	300	45	18
DT95-16	120K	80K	4	1½"	18	28	7	16" x 65"	24" x 41"	530	60	24
DT95-18	150K	100K	5	1½"	27	34	9	18" x 65"	24" x 41"	500	75	30
DT95-21	210K	140K	7	1½"	36	42	12	21" x 62"	24" x 50"	560	105	42
DT95-24	300K	200K	10	1½"	42	50	15	24" x 72"	30" x 50"	850	150	60

