

*A Quality Water Conditioner  
from Hydroflo*



### Features Include:

- 💧 Non-Corrosive—poly mineral tank, thermo plastic brine tank.
- 💧 Noryl Valve reinforced with fiberglass.
- 💧 Controller—easily programmed to family demands—guest switch for extra demand.
- 💧 Automatic Bypass—water available even during regeneration.
- 💧 High Capacity Resin.



**Personal Care**

Baths, showers, shampoos and shaving are all wonderful new experiences with soft water because there are no hard water impurities to leave a sticky soap film. A soft water rinse removes residue, leaving skin smoother, feeling cleaner.

**Easier Cleaning - Saves You TIME and EFFORT!**

Windows, porcelain, ceramic tile, chrome fixtures, painted surfaces, counter tops, linoleum floors — everything comes clean with less effort than you'd believe possible. And they stay clean longer because soft water doesn't leave that dulling soap film.

**Brighter Wash**

Laundry soaps and detergents work better in soft water to wash clothes their brightest. They come out cleaner — softer, too, because soft water leaves virtually no soap residue in the fabric.

**Sparkling Dishes**

Washed by hand or in the dishwasher, glassware sparkles, dishes and china come squeaky clean and silver shines its brightest.

**Save Money**

You'll spend less on soap, detergent, shampoo, cleaning aids and personal care products because you use smaller amounts. And you can stop buying additives like packaged water softeners.

**Protect Appliances, Plumbing**

Dissolved minerals in hard water form a scale that can ruin water heaters, plumbing and water-using appliances. Soft water controls the build-up of hard water scale.

**Specifications for C240 and C240M**

Grains Capacity Max./Min.	24,000/16,000
Mineral (Cu. Ft./Lbs.)	0.75/41
Mineral Brine Tank Size	9" x 35"
Brine Tank Size	13" x 20" x 44"
Brine Tank Capacity (Lbs.)	250
Salt Lbs. Per Regeneration	
Max./Min.	14/5
Service Flow (gpm)	5
Backwash Rate (gpm)	1.5
Max. Pressure Drop (psi)	10
Pipe Size	3/4"
Max. Pressure (psi)	125
Max. Temperature	100°F
Floor Space	13" x 20"



C240 Control



C240 M Control



256 Noryl Bypass is included

When used on water supplies containing iron. Hydroflo SBS should be added when regenerating.