



*The Automatic Neutralizer & Iron removal filter...
Two Units in one from Hydroflo*

The **70 FILTER** has been designed to facilitate the removal of some concentrations of Iron and suspended particulated matter as well as neutralization of acidic water conditions. The corrosive water first passes through the units top stage where it neutralizes the water, oxidizes and filters out the Ferric Iron. The water then flows into the bottom stage where Ferrous and remaining Ferric Iron is removed.

Features Include:

- Non-Corrosive—poly mineral tank, therm plastic brine tank—Noryl valve reinforced with fiberglass.
- Six-Day Controller—easily programmed to family demands—guest switch for extra demands.
- Automatic Bypass—water available even during regeneration.
- Top Quality, Long Life Neutralization Media (Hydroflo Calcite, not included).
- Convenient Dome Hole with cap for accessibility when replacing media.



*Live Better With A HYDROFLO 70 FILTER
Automatic Iron filter and Neutralizer, All In One Unit*



70 Filter



1256 Noryl Bypass is included

Specifications

70 FILTER

Mineral Top (Cu. Ft. /Lbs.)	0.75/70
Mineral Bottom (Cu. Ft. /Lbs.)	1.0/100
Tank Size Top	10" x 33"
Tank Size Bottom	10" x 33"
Brine Tank Size	15" x 17" x 33"
Brine Tank Capacity (Lbs.)	250
Max. Pressure Drop (psi)	10
Service Flow (gpm)	7
Backwash Rate (gpm)	4.0
Pipe Size	3/4"
Max. Pressure (psi)	125
Max. Temperature, F°	100°
Floor Space	15" x 27"

Hydroflo Calcite in the 70 FILTER must be replaced approximately every 18-24 months.